SAVEOMAT DOS GRAVIMETRIC DOSING STATION





INDEX

iNOEX GmbH Maschweg 70 D-49324 Melle

sales@inoex.de www.inoex.de

SAVEOMAT DOS GRAVIMETRIC DOSING STATION

GENERAL FEATURES

- Suitable for complex product recipes and special applications (up to 7 components)
- Individual and flexible configuration possible (also with no main component and 6 side components)
- Funnel weigher sizes of main and side components freely selectable
- Granules and powder versions
- Easy access to and cleaning of all components
- Constant mass throughput with material savings of up to 5 %
- Constant weight per metre, reduced to an absolute minimum
- Reduced start-up scrap
- Optimum material flow behaviour
- Dead zone free filling, weighing and dosing
- Ready for Industry 4.0 for comprehensive collection and analysis of production data







MADE IN GERMANY

Main component	Mass throughput [kg/h]
НК 200	2 – 200
НК 350	10 – 350
HK 500	10 – 500
HK 750	20 – 750
HK 1000	50 – 1000
HK 1400	50 - 1400
HK 1600	100 - 1600
HK 1800	100 - 1800
HK 2000	100 – 2000
HK 2500	100 – 2500

Side component	Mass throughput [kg/h]
NK 20	0,2 – 20
NK 60	0,8 – 60
NK 200	2 – 200
NK 350	10 – 350
NK 500	10 - 500
NK 750	20 – 750